

Insect Trapping

โคมดักแมลง รุ่น ECHOLIGHT 180



specification

* เหมาะสำหรับ สำหรับศูนย์อาหาร , ร้านอาหาร, Mini Mart , ร้านกาแฟ , ไลน์ผลิตอาหาร

ขนาดตัวเครื่อง กว้าง x ยาว x สูง

54 ซม. x 17 ซม. x 20 ซม.

น้ำหนัก

1000 กรัม

กำลังไฟฟ้า

36 วัตต์

หลอดยูวีล่อแมลง

OSRAM DULIX BLUE UVA

ขนาดแผ่นการ

18 ซม. x 42 ซม.

พื้นที่ดักจับแมลง

180 องศา

ครอบคลุมพื้นที่ใช้งาน

100 ตารางเมตร

*ป้องกันการมองเห็นเศษซากของแมลง

Insect Trapping

โคมดักแมลง รุ่น ECHOLIGHT BLACK TRAP



specification

* เหมาะสำหรับ สำหรับศูนย์อาหาร , Mini Mart , ไลน์ผลิตอาหาร , ห้องอาหาร , ร้านกาแฟ

ขนาดตัวเครื่อง กว้าง x ยาว x สูง

54 ซม. x 15 ซม. x 20 ซม.

น้ำหนัก

1000 กรัม

กำลังไฟฟ้า

36 วัตต์

หลอดยิววีล่อแมลง

OSRAM DULIX BLUE UVA

ขนาดแผ่นการ

47 ซม. x 19 ซม.

พื้นที่ดักจับแมลง

180 องศา

ครอบคลุมพื้นที่ใช้งาน

100 ตารางเมตร

*ป้องกันการมองเห็นเศษซากของแมลง



Actinic BL PL-S/PL-L

PL-L 36W/10/4P 1CT/25

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL(-K)/TL-D(-K)/TL-E/PL-S and PL-L lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice. Furthermore, the availability of a wide range of form factors (straight (T5, T8, T12), circular (TL-E) and compact (PL-S/PL-L)) and wattages enables you to make all kinds of designs for your electronic fly killers.

Product data

General Information	
Cap-Base	2G11 [2G11]
Main Application	Insect traps
Life to 50% Failures (Nom)	11000 h

Light Technical	
Color Code	210 [leadfree 360 glass (10)]
Chromaticity Coordinate X (Nom)	220
Chromaticity Coordinate Y (Nom)	215
UV Depreciation at 2000 h	15 %
UV Depreciation at 5000 h	20 %

Operating and Electrical	
Power (Rated) (Nom)	36 W
Lamp Current (Nom)	0.435 A
Voltage (Nom)	106 V

Mechanical and Housing	
Cap-Base Information	4 Pins

Approval and Application	
Mercury (Hg) Content (Max)	2.1 mg
Mercury (Hg) Content (Nom)	2.0 mg

UV	
UV-A Radiation 100Hr (IEC)	8.5 W


Product Data	
Full product code	871150026481740
Order product name	PL-L 36W/10/4P 1CT/25
EAN/UPC - Product	8711500264817
Order code	927903421007
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	927903421007
Net Weight (Piece)	104.000 g

Actinic BL PL-S/PL-L

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




PL-L 36W/210/4P

Product	D1 (max)	D (max)	A (max)	B (max)	C (max)
PL-L 36W/10/4P ICT/25	18 mm	39 mm	384.2 mm	410 mm	416.6 mm

Photometric data



Lightcolor /10, /110 & /210



Lightcolor /10, /110 & /210

